



# Integrated Type Keyless Drill Chucks VERTEX®

KEYLESS DRILL CHUCK

ORDER NO.	Clamping Capacity		Female Taper DIN or Jacobs	OUTER Ø / mm	Length		WEIGHT (kgs)	CODE NO.
	Ø mm	Ø inch			Open B mm	Closed A mm		
INT-8-MT-2	0.5-8	0-5/16"	MT-2	35	140	148	0.8	3301-030
INT-8-JC-20	0.5-8	0-5/16"	JC-20	35	124	132	0.8	3301-031
INT-8-BT30	0.5-8	1/64"-1/8"	BT30	35			1	3301-070
INT-8-BT40	0.5-8	1/64"-1/8"	BT40	51.5			1.5	3301-072
INT-8-NT30	0.5-8	1/64"-1/8"	NT30	51.5			0.8	3301-080
INT-8-NT40	0.5-8	1/64"-1/8"	NT40	51.5			1.3	3301-081
INT-8-SK40	0.5-8		SK-40	51.5	81	90	1.4	3301-083
INT-8-SK50	0.5-8		SK-50	51.5	80	88	0.7	3301-086
INT-13-R8	1-13	1/64"-1/2"	R8	51.5	175	183	1.5	3301-032
INT-13-MT2	1-13	0-1/2"	MT-2	51.5	172	184	1.3	3301-082
INT-13-MT3	1-13	0-1/2"	MT-3	51.5	182	194	1.4	3301-033
INT-13-MT4	1-13	0-1/2"	MT-4	51.5	182	194	1.8	3301-034
INT-13-JC-20	1-13	0-1/2"	JC-20	51.5	138	150	1.4	3301-035
INT-13-JC-25	1-13	0-1/2"	JC-25	51.5	138	150	1.6	3301-036
INT-13-JC-32	1-13	0-1/2"	JC-32	51.5	138	150	1.8	3301-037
INT-13-NT30	1-13	0-1/2"	NT-30	51.5	138	150	1.4	3301-038
INT-13-NT40	1-13	0-1/2"	NT-40	51.5	98	109	1.8	3301-039
INT-13-BT30	1-13	1/64"-1/2"	BT30	51.5			1.4	3301-071
INT-13-BT40	1-13	0-1/2"	BT-40	51.5	95	106	2	3301-040
INT-13-BT50	1-13	0-1/2"	BT-50	51.5	105	116	4.7	3301-041
INT-13-NT50	1-13	0-1/2"	NT-50	51.5			4.3	3301-059
INT-13-SK30	1-13		SK-30	51.5	98	104	1.34	3301-084
INT-13-SK40	1-13		SK-40	51.5	99	111	1.9	3301-085
INT-13-SK50	1-13		SK-50	51.5	93	106	3.9	3301-087
INT-16-R8	3-16	1/8"-5/8"	R8	58	188	202	1.9	3301-042
INT-16-MT3	3-16	1/8"-5/8"	MT3	58	188	202	1.9	3301-043
INT-16-MT4	3-16	1/8"-5/8"	MT4	58	188	202	2	3301-044
INT-16-JC-20	3-16	1/8"-5/8"	JC-20	58	140	155	1.8	3301-045
INT-16-JC-25	3-16	1/8"-5/8"	JC-25	58	150	165	1.7	3301-046
INT-16-JC-32	3-16	1/8"-5/8"	JC-32	58	150	165	2.2	3301-047
INT-16-NT40	3-16	1/8"-5/8"	NT-40	58	116	130	2.6	3301-049
INT-16-BT40	3-16	1/8"-5/8"	BT-40	58	116	130	2.5	3301-050
INT-16-BT50	3-16	1/8"-5/8"	BT-50	58	126	140	5	3301-051
INT-16-NT50	3-16	1/8"-5/8"	NT-50	58			4.5	3301-056
INT-16-SK40	3-16	1/8"-5/8"	SK-40	56		127	2.4	3301-057
INT-16-SK50	3-16	1/8"-5/8"	SK-50	56		98	3.9	3301-058

ORDER NO.	SIZE DIN 69871A	SAME SIZE	Clamping range (Ømm)	D	L		WEIGHT (kg)	CODE NO.
					Minimum	Maximum		
SK-511	SK40-APU08	INT-8-SK40	0.5-8	35.6	81	90	1.4	3301-001
SK-512	SK40-APU13	INT-13-SK40	1-13	52	99	111	1.9	3301-002
SK-514	SK50-APU13	INT-13-SK50	1-13	52	93	106	3.9	3301-004
SK-509	SK50-APU08	INT-8-SK50	1-13	35.6	80	88	0.7	3301-005
SK-510	SK30-APU13	INT-13-SK30	1-13	52	98	104	1.34	3301-006
SK-515	SK40-APU16	INT-16-SK40	3-16	56.8	127	140	2.4	3301-007
SK-516	SK50-APU16	INT-16-SK50	3-16	56.8	98	111	3.9	3301-008

ORDER NO.	Clamping Capacity		Taper	OUTER Ø / mm	WEIGHT (kgs)	CODE NO.
	mm	inch				
INT-8-CAT30	0.5-8	1/64"-1/8"	CAT30	Ø35	0.8	3301-073
INT-13-CAT30	0.5-13	1/64"-1/2"		Ø51.5	1	3301-074
INT-8-CAT40	0.5-8	1/64"-1/8"	CAT40	Ø35	1.32	3301-075
INT-13-CAT40	0.5-13	1/64"-1/2"		Ø51.5	2.1	3301-076
INT-16-CAT40	3-16	1/8"-5/8"	CAT50	Ø58	2.26	3301-077
INT-13-CAT50	0.5-13	1/64"-1/2"		Ø51.5	3.95	3301-078
INT-16-CAT50	3-16	1/8"-5/8"	Ø58	4.2	3301-079	